Pioneer sound.vision.soul

Service Manual

ORDER NO.
TRT1145

STEREO HEADPHONES

SE-A1000 /XCN1/E

SE-M280 /XCN1/E

CONTENS

1.SE-A1000 1

2. SE-M280 2

3. SPECIFICATIONS 2

PIONEER CORPORATION 4-1, Meguro 1-chome, Meguro-ku, Tokyo 153-8654, Japan
PIONEER ELECTRONICS (USA) INC. P.O. Box 1760, Long Beach, CA 90801-1760, U.S.A.
PIONEER EUROPE NV Haven 1087, Keetberglaan 1, 9120 Melsele, Belgium
PIONEER ELECTRONICS ASIACENTRE PTE. LTD. 253 Alexandra Road, #04-01, Singapore 159936

©**PIONEER CORPORATION 2005**

MAY. 2005 printed in Japan

SE-A1000 / SE-M280

1. SE-A1000

1.1 PARTS LIST

Mark	No.	Description	Parts No.
	1	Ear Pad	WNV1118
	2	Plug Adaptor	WKX1035

1.2 EXPLLOED VIEW

Packing View

2. SE-M280

2.1 PARTS LIST

Mark	No.	Description	Parts No.
	1	Ear Pad	WNV1103
	2	Plug Adaptor	WKX1036

2.2 EXPLLOED VIEW

Packing View

3. SPECIFICATIONS

Model	Frequency responce	Impedanc	Maximum Input power	Sensitivity	Driver unit	Plug	Cord	Weight (Without cord)
SE-A1000	10 ~30,000Hz	45Ω	1,500mW(JEITA)	102dB/mW	Φ50 mm	W	6.0m	280 g
SE-M280	5 ~25,000Hz	32Ω	1,200mW(JEITA)	102dB/mW	Φ40 mm	W	3.5m	225 g

Plug form : S (straight type) / L (L type) / W (2Way plug)